

Grandstream Device Configuration

STATUS

BASIC SETTINGS

ADVANCED SETTINGS

FXS PORT

Admin Password: (purposely not displayed for security protection)

802.1Q/VLAN Tag (0-4094)

Layer 2 QoS: SIP 802.1p (0-7)

RTP 802.1p (0-7)

STUN server is: (URI or IP:port)

Keep-alive Interval: (in seconds, default 20 seconds)

Use STUN to detect network connectivity:

- No
 Yes, total STUN response misses to restart DHCP (minimum=3)

Use DNS to detect network connectivity:

- No Yes

Firmware Upgrade and Provisioning:

Upgrade Via TFTP HTTP HTTPS

Firmware Server Path:

Config Server Path:

XML Config File Password:

HTTP/HTTPS User Name:

HTTP/HTTPS Password:

- Always send HTTP Basic Authentication Information
 Send HTTP Basic Authentication Information only when challenged

Firmware File Prefix:

Firmware File Postfix:

Config File Prefix:

Config File Postfix:

Allow DHCP Option 66 to override server:

- No Yes

Automatic Upgrade:

- No Yes, every minutes(30-5256000).
 Yes, daily at hour (0-23). Yes, weekly on day (0-6).

- Always Check for New Firmware at Boot up
 Check New Firmware only when F/W pre/suffix changes
 Always Skip the Firmware Check

Disable SIP NOTIFY Authentication: No Yes (Device will not challenge NOTIFY with 401 when set to Yes)

Authenticate Conf File: No Yes (cfg file would be authenticated before acceptance if set to Yes)

SIP TLS Certificate:

SIP TLS Private Key:

SIP TLS Private Key Password:

ACS URL:

ACS Username:

ACS Password:

Periodic Inform Enable: No Yes

Periodic Inform Interval:

Connection Request Username:

Connection Request Password:

CPE SSL Certificate:

CPE SSL Private Key:

Country Specific Deployment:

System Ring Cadence:

Dial Tone:

Ringback Tone:

Busy Tone:

Reorder Tone:

Call Progress Tones:

Confirmation Tone:

Call Waiting Tone:

Prompt Tone:

Syntax: f1=val [, f2=val [, c=on1/off1 [-on2/off2 [-on3/off3]]]]; (Frequencies are in Hz and cadence on and off are in ms)

Prompt Tone Access Code:

(Key pattern to get Prompt Tone. Maximum 20 digits. No default.)

Lock Keypad Update: No Yes (configuration update via keypad is disabled if set to Yes)

Disable Voice Prompt: No Yes (voice prompt is disabled if set to Yes)

Disable Direct IP Call: No Yes (direct IP call is disabled if set to Yes)

NTP Server: (URI or IP address)

Allow DHCP option 42 to override NTP server: No Yes

Syslog Server:

Syslog Level:

Send SIP Log: No Yes

Download Device Configuration:

Upload firmware: